



**Application and Sales Office:**

29235 Lorie Ln. PO Box 1013

Wixom, MI 48393-1013


Phone 248-344-7236

Fax 248-344-9401

E-Mail: tbradley@cdims.com

**CDH-R-148-ARID-Dry Units**

<u>Model</u>	<u>CFM</u>	<u>Fuel Type</u>	<u>"A" Dim.</u>	<u>"B" Dim.</u>	<u>"C" Dim.</u>	<u>Weight</u>
CDH-R-148	7,500	Gas or Electric	158"	62 1/2"	85"	6800 lbs
CDH-R-148	7,500	Dual	180"	62 1/2"	85"	7700 lbs



Air Volume	Static Pressure External	Moisture Removal Lbs/Hr 80°/60% RH	Moisture Removal Gallons/Day 80°/60% RH	Moisture Removal Lbs/Hr 55°/80% RH	Moisture Removal Gallons/Day 55°/80% RH	Moisture Removal Lbs/Hr 40°/80% RH	Moisture Removal Gallons/Day 40°/80% RH
7,500	2.0	210	605	175	504	121	348

Pipe Size	LP Inlet Pressure	Natural Gas Inlet Pressure	Electric Reactivation Load 230/1/60	Electric Reactivation FLA Load 460/3/60	Gas Reactivation FLA Load 460/3/60	CFH Gas Max Usage NG	Gallon/HR Max Usage LP
1"	7-14" w.c.	7-14" w.c.	N/A	200	17	600	6.33



**Available Accessories:**

- Remote Humidstat
- Cooling Coil Modules
- Heating Coil Modules
- Trailer Mounting
- (2) 18" or 20" Round Connections
- 5.0 Static Pressure External